

GLS™ TPE
MAJOR HOME APPLIANCE SOLUTIONS

ENHANCE APPLIANCE PERFORMANCE WITH TPEs FOR ANTI-VIBRATION FEET

In the highly competitive home appliance market, brands are driving to differentiate products with enhanced performance attributes. GLS TPEs are designed to help you stand out from your competitors with reduced appliance movement and noise.

Anti-vibration feet made with our TPEs have resistance to wear and tear, better performance and function, improved processability and reduced number of part defects.

	VERSAFLEX™ VDT 4202-40B	DYNAFLEX™ G7940-1
Application	Anti-Vibration Feet	Anti-Vibration Feet
Defining Characteristic	Vibration Damping	Good Processability
Compression Set	Low Compression Set	Low Compression Set
Tactile Feel	Grippy Feel	Soft Touch, Rubbery Feel
Coloring	Black	Natural
Hardness	40 Shore A	40 Shore A
Processing	Injection Molding	Injection Molding
Overmolding Substrate	Polypropylene	Polypropylene



HOW GLS TPES MAKE THE DIFFERENCE IN HOME APPLIANCE ANTI-VIBRATION FEET

- **Reduced appliance movement and noise** – vibration damping technology reduces movement and noise of the appliance when in use
- **Resistance to wear and tear** – TPes are proven to maintain their shape and resist tears with low compression set
- **Better performance and function** – increase design freedom with material selection flexibility
- **Improved processability** – boost efficiency with injection molding processing and reduce overall production cycle time and costs
- **Reduced number of part defects** – eliminate secondary operations to achieve consistent and controlled results

To learn more about GLS TPes home appliances, visit www.avient.com or call +1.844.4AVIENT (1.844.428.4368).

www.avient.com



Copyright © 2020, Avient Corporation. Avient makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as “typical” or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Avient makes no warranties or guarantees respecting suitability of either Avient’s products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. AVIENT MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.